

Product Information

ISO Class 4 - 5

Cleanroom Class 10 - 100 EU Grade A/B/C/D

Sterile SatPax® 1200

Sterile Pre-wetted Cleanroom Laundered 100% Polyester Knit Wiper

Sterile SatPax® 1200 combines Super Polx® 1200 cleanroom effective and easy to use solution versus traditional bulk sterile to a 10⁶ Sterility Assurance Level making the laundered wipers composed of 100% continuous filament polyester knit fabric with a high saturation level of 70% IPA and 30% DI water. This pre-wetted format provides a cost

handling of solvents, maintenance of squirt bottles and inconsistent wetting and cleaning associated with wetting environments. a dry wiper. Each package is then gamma irradiated

product ideal for cleaning critical sterile processing



Other Sterile Pre-wetted wipers

Sterile SatPax® MicroSeal® WFI

Sterile SatPax® 670

Sterile SatPax® 1000

Key Attributes

- 100% continuous filament polyester knit
- Laundered and packaged in Berkshire's ISO Class 4 cleanroom
- Pre-wetted with consistent 70% IPA/ 30% DI Water to a high saturation level
- Re-sealable solvent resistant packaging
- Wipers in j-folded configuration for single withdrawal
- Gamma irradiated and sterile validated to a 10⁻⁶ Sterility Assurance Level per AAMI guidelines
- Certificate of Sterility with each case and available on the web by lot number 24/7. Details: Expiration Date, Radiation Dosage, Lot Information, Meets cGMP requirements for traceability

Benefits

- Very low fibers, particles, ions and extractables
- High abrasion resistance
- Reduces alcohol usage and preparation / handling costs
- Reduces VOC emissions
- Increases cleaning efficiency
- Increases cleaning protocol consistency

Environmental

- Reduces VOC (Volatile Organic Compound) emissions
- Complies with RoHS
- Registered under REACH

Applications

- Designed for use in ISO Class 4 and higher sterile cleanroom environments
- Designed for use in wet cleaning of critical surfaces where control of flammable solvents and flammable solvent concentrations is required
- Final cleaning of surfaces or products prior to manufacturing or packaging
- High saturation level is ideal for removing cleaning and disinfecting residues in sterile environments

Saturation Levels

The amount of solution contained in each wiper can be varied according to customer requirements. Higher saturation levels apply more solution to the surface during cleaning.

Validated Sterile

ANSI/AAMI/ISO procedures have been followed for verification of irradiation dose with audits being performed to monitor bioburden levels and dose. The Sterility Assurance Level (SAL) or the probability of a viable organism being present on a product unit after sterilization is a SAL of 10⁻⁶ (which is the chance of 1 non-sterile unit in 1,000,000).

www.berkshire.com

Contact: Tel 1 800 242 7000 / 1 413 528 2602 info@berkshire.com

Americas	Tel 1 413 528 2602	Fax 1 413 528 2614	info@berkshire.com
Europe	Tel 44 (0) 870 757 2877	Fax 44 (0) 870 757 2878	enquiries@berkshire.uk.com
SE Asia	Tel 65 6252 4313	Fax 65 6252 4312	enquiries@berkshire.com.sg
Japan	Tel 81 3 5827 2380	Fax 81 3 5827 2382	master@berkshire.co.jp



Technical Data (In Dry State)

Attribute		Units	Value	Test Method
Basis Weight		g/m²	151	TAPPI T-410
Caliper		μm	521	TAPPI T-411
Fibers	≥100µm	fibers/cm ²	0.35	IEST-RP.CC004.3, Sec 6.1.3 / Sec 6.2.2
Particles	≥0.5µm	x10 ³ /cm ²	0.22	IEST-RP.CC004.3, Sec 6.1.3 / Sec 6.2.1
Sorbency	Capacity	mL/m²	509	IEST-RP.CC004.3, Sec 8.1 modified / Sec 8.2 modified
	Efficiency	mL/g	3.4	
	Rate	seconds	1	
Non-Volatile Residue	DI Water	g/m²	0.0045	IEST-RP.CC004.3, Sec 7.1.2
	IPA	g/m²	0.0092	
lons	Na ⁺	ppm	0.17	IEST-RP.CC004.3, Sec 7.2.2
	K ⁺	ppm	0.010	
	Ca ⁺⁺	ppm	0.053	
	Mg ⁺⁺	ppm	0.011	
	CI ⁻	ppm	0.39	

Notes:

- Technical data represented in this table are typical values at the time of publication. These should not be used as
 product specifications.
- Due to differences in test methods applied and equipment utilized by different wiper manufacturers, valid product comparisons may only be obtained through side-by-side testing in the same test facility, under similar conditions
- Third party testing can be performed upon request

Order Information:

Product	Number	Size	Shts/pk	Pks/cs	IPA/DI	Saturation	VOC % by Weight	Style
Sterile SatPax® 1200	SSP120000312	9x9" (23x23cm)	30	12	70/30	60%	40.9%	J-fold

Other Berkshire Products



Wipers



Glove Liners



Documentation Systems



Swabs

